

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
14 October 2004 (14.10.2004)

PCT


(10) International Publication Number
WO 2004/086979 A1

- (51) International Patent Classification⁷: **A61B 10/00**,
B01L 3/00, C12M 1/30, A61M 35/00
- (21) International Application Number:
PCT/EP2004/003392
- (22) International Filing Date: 31 March 2004 (31.03.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
MI2003A000643 1 April 2003 (01.04.2003) IT
- (71) Applicant (for all designated States except US): **COPAN INNOVATION LIMITED [IE/IE]**; 6 O'Curry Street, Limerick (IE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **TRIVA, Daniele** [IT/IT]; Via dei Prati 22/A, I-25073 Bovezzo (IT).
- (74) Agent: **APPOLONI, Romano**; Notarbartolo & Gervasi S.p.A., Corso di Porta Vittoria, 9, I-20122 Milan (IT).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: **SWAB FOR COLLECTING BIOLOGICAL SPECIMENS**

(57) Abstract: The present invention relates to a swab (20) for collecting biological specimens of the type consisting of a rod (14) terminating in a tip (16) covered with fibre (17) with hydrophilic properties to allow absorption of said specimens, characterised in that said fibre (17) covers said tip (16) in the form of a layer deposited by flocking.



Foreign Cite No. 4
Appl No. 10/578935
August 9, 2006
Robert S. Salter
0656-032US3A

WO 2004/086979 A1



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

SWAB FOR COLLECTING BIOLOGICAL SPECIMENS

Field of the invention

The present invention relates to a swab for collecting biological specimens.

Background of the invention

5 In the field of clinical and diagnostic analyses, swabs for collecting biological specimens of organic material are known, consisting essentially of a cylindrical rod around one end of which, known as the tip, is wrapped a wad of fibre such as rayon or a natural fibre such as cotton, with hydrophilic properties to allow rapid absorption of the quantity of specimen to be collected and tested. Stable
10 adherence of the fibre wrapped around the tip of the rod is generally achieved by gluing.

Usually, especially if the specimen is to be examined by culturing the microorganisms gathered with the collection, a swab is immersed in a test-tube containing culture medium immediately after collection for appropriate
15 conservation of the specimen during storage and /or transport thereof to the analytical laboratory.

An example of this type of device is given in patent EP0643131 by the same Applicant and refers to a swab for collecting and *in vitro* transporting specimens, of the type comprising a test-tube with culture medium in gel form and a rod
20 carrying at one end a stopper for sealing the test-tube and at the opposite end means for collecting said specimen, for example a wad of fibre wrapped around the tip of the rod, to be dipped into the culture medium.

The tip of the cylindrical rod, generally manufactured from essentially rigid material such as plastic, for example by extrusion, commonly presents a truncating cut
25 which would make it difficult to insert the swab rod into the cavities (oral, nasal, ocular or rectal, urethral, vaginal etc.) of the patient from whom the specimen is taken, if the tip is not adequately protected. Therefore, the wad of hydrophilic fibre wrapped around said truncated end must not only contain sufficient material to allow absorption of the specimen in the desired quantity, in general 100
30 microlitres, but must also have a sufficiently thick and rounded shape to sheathe the edge of the truncated end so that it cannot cause damage or irritation to the patient during specimen collection. For this reason the fibre wad is wrapped

around the tip of the rod in a rounded shape, typically developing into an ogive or similar shape so that it gradually becomes thicker towards the end of the rod thus reaching maximum thickness and therefore maximum protective effect, precisely around the truncated end. A wad of such a shape, while protecting the patient
5 from any risk of contact with said truncated end of the rod, results in a number of drawbacks. The main one is that the thickness of the wad, because of the hydrophilic nature of the fibre, leads to penetration of collected liquid specimen into the mass of said wad. As, for practical reasons, the sample is released from the swab at the moment of analysis by simply gripping the rod of the swab and
10 delicately sliding its tip and hence the fibre impregnated with liquid, along for example a petri dish with culture medium, in practice by spreading the specimen onto this latter (swabbing), even if this operation is repeated and is careful, it does not enable the entire volume e.g. the 100 ml of absorbed specimen to be released, because that part of it which has penetrated into the interior of the wad
15 in the direction of its tip cannot be pressed out towards the surface and hence released by the swab during this operation

Due to this defect, on average only about 40% of the liquid specimen collected can in practice be recovered for analysis. Such loss of specimen translates inevitably into reduced sensitivity of analysis and increased false negatives. In
20 this respect, referring to the aforementioned average specimen loss after swabbing the swab, by testing only the 40 microlitres released for swabbing out of the 100 microlitres of specimen initially collected, it becomes difficult to establish whether a negative test effectively refers to the absence of the microorganism sought or rather to its non- or insufficient transfer from swab to test plate.

25 A further problem derived from the bulky fibre wad of a swab of the known art is particularly evident for example in the case of urethral or ocular use of said swab. In these and other particular applications it would actually be even more desirable to be able to minimize swab thickness and hence patient discomfort during collection.

30 **Summary of the invention**

As a solution to these problems, and also to achieve other advantages which will be apparent from the description, the present invention proposes a swab for

collecting biological specimens of the type consisting of a rod terminating with a tip covered in fibre with hydrophilic properties to allow absorption of said specimens, characterised in that said fibre covers said tip in the form of a layer applied by means of flocking.

- 5 With the aim of better understanding the characteristics and advantages of the invention, a non-limiting example of a practical embodiment thereof is described hereinafter, with reference to the figures of the accompanying drawings. Said example refers to the case of a swab suitable for both the collection and storage of a biological specimen, and therefore also includes a test-tube containing a culture medium suitable for the collected microorganisms into which the swab is to be immersed after collection, such as for example the type described in the
10 aforementioned patent EP0643131 by the same Applicant.

Brief description of the figures

- Figure 1 shows an exploded view of the two components of a device in accordance with the example, that is the swab and test-tube, whereby the test-tube is partially sectioned longitudinally.
15

Figure 2 shows an enlarged detail of the swab of Figure 1 in section.

Detailed description of the invention

- With reference to said figures, a device of the invention in accordance with the illustrated example comprises an essentially cylindrical test-tube 10 containing a culture medium in gel form 11, presenting a free surface level 12 inside the test-tube.
20

The upper open end of the test-tube presents a collar 13 for receiving a closure means.

- 25 The device is completed by a swab 20 consisting of a rod 14 carrying at one end a stopper 15 which has to act as the closure means of the test-tube and is hence shaped so that it can engage, for example by snap-engaging, with the collar 13 of the test-tube.

- At the opposite end, the rod 14 terminates with a tip 16 carrying a suitable means, for example a layer of fibre 17, for collecting the specimen to be analysed. In the
30 illustrated example, said tip 16 of the rod is shaped in a rounded geometry, similar to an ogive, and said fibre 17 being disposed as a layer of uniform thickness.

In general terms, in accordance with the fundamental characteristic of the invention, said fibre with hydrophilic properties is deposited by means of flocking.

The flocking technique is preferably of the type conducted in an electrostatic field which deposits the fibres in an ordered manner, perpendicular to the surface of the tip of the swab rod, which has been previously coated with adhesive for example by immersion or spraying.

The fibre which is to form the flocked layer is subjected to an electrostatic field, and is hence deposited in an oriented manner and anchored to the surface of the tip, being retained by the adhesive.

10 The adhesive is preferably water-based: once dried it enables the fibre to be anchored in a stable manner to the swab and to resist abrasion.

The flocked swab is then dried by exposing it to a source of heat or radio-frequency.

The tip of the swab stem is covered with a layer of fibre, preferably of uniform thickness, and from 0.6 to 3 mm thick. The fibre count, i.e. the weight in grams per 100 linear metres of a single fibre, is preferably between 1.7 and 3.3 Dtex. In particular, a fibre of 0.6 mm length and 1.7 Dtex can be applied by flocking to obtain a fine nap, and a fibre up to 3 mm in length and 3.3 Dtex can be applied to obtain a long nap, obtaining, for values intermediate between the aforedefined, corresponding intermediate characteristics of thickness and fineness of the flocked layer.

Within the wide choice of such values, the expedient to be respected according to the objects of the invention is to maintain an ordered arrangement of the fibres, substantially parallel to each other and normal to the surface of the rod, avoiding any overlapping of fibres which can occur if the nap is too long. Indeed, in this manner the capillary represented by each fibre, by virtue of which it can carry out its task of absorbing and releasing essentially the same quantity of specimen, remains unimpaired and functional.

The amount of fibre to be deposited for forming the flocked layer in accordance with the invention is determined on the basis of the type of fibre and the pre-chosen layer characteristics of thickness and fineness, in such a manner as to enable 100 microlitres of specimen to be absorbed.

In accordance with the objects of the invention, the fibre is chosen from a wide range of materials provided they are hydrophilic by capillarity, such as for example, synthetic or artificial materials e.g. rayon, polyester, polyamide, carbon fibre or alginate, natural materials e.g. cotton and silk, or mixtures thereof.

5 Examples

Some preparative examples are now given of a swab according to the invention. Such examples are not intended in any way to limit the scope of the invention.

EXAMPLE 1

A swab is prepared using a plastic rod, suitable for human clinical collection, of
10 diameter 2.5 mm which decreases to 1 mm over a length of about 6 cm.

The tip of the part with the smallest diameter is dipped in or sprayed with an adhesive, then the rod is placed vertically in a flocking apparatus in electrostatic field to deposit a polyamide flock.

The polyamide flock of 0.7 mm length and 1.7 Dtex allows 0.5 μl per mm^2 to be
15 absorbed, therefore by flocking the 10 mm long tip of said rod the absorbing capacity obtained is 40 μl .

EXAMPLE 2

Proceeding as per example 1, a rod with a spatulate end is used, suited for
example to collecting organic specimens from the oral cavity of a patient.
20 Polyester fibre of 1 mm length and 1.7 Dtex count are used for the flocking.

EXAMPLE 3

Proceeding as per examples 1 and 2, polyester fibre of 2 mm length and 2.5 Dtex count is used.

Continuing in general terms, it is calculated that a swab of the invention is capable
25 of releasing about 90% of the absorbed specimen by swabbing, in this manner considerably increasing the sensitivity of the analysis compared with swabs of the known art, in particular by almost completely eliminating the risk of false negatives resulting from the incomplete release of the collected specimen from swab to test plate.

30 In addition, the fact of being able to form, according to the invention, a fibre layer of any thickness, even very small, around the tip of the rod rather than a mass to cover it, as in the known art, means that the required rounded shape of the swab,

i.e. free of edges, no longer has to depend on the mass of fibre itself but on the tip of the rod, which can therefore be preferably shaped into a round form, as indeed occurs in the aforescribed example and shown in the accompanying drawings. Particularly in specific cases where swabs of the greatest possible thinness are required, for example urethral or ocular, this represents a further definite advantage over known swabs. Indeed a swab can be provided with a rounded tip by virtue of its shaping, around which a thin layer of fibre is deposited by flocking to allow on the one hand collection of a sufficient quantity of specimen for analysis, and on the other to minimize the total bulk of the part of the swab which is to penetrate the urethra, in consequence so reducing the discomfort of the patient undergoing the collection procedure.

The shape given to the tip of the swab nevertheless varies greatly according to the type of collection it is intended for, and can even be truncated or have edges when the type of collection (for example oral) allows it.

According to the invention, the type of adhesive, type of fibre and fibre characteristics, such as length and count, are in any case chosen from a wide range of options in order to obtain an ideal specific marker for identifying the microbiological specimen, whether by a direct diagnostic technique, by immuno-test, or by molecular biology techniques such as PCR, or with other known culturing, enrichment or selection techniques.

The specimen to be collected with a swab of the invention generally consists of bacteria or viruses or DNA or RNA or a mixture thereof.

CLAIMS

1. Swab (20) for collecting biological specimens of the type consisting of a rod (14) terminating in a tip (16) covered with fibre (17) with hydrophilic properties to allow absorption of said specimens, characterised in that said fibre (17) covers said tip
5 (16) in the form of a layer deposited by flocking.
2. Swab as claimed in claim 1, characterised in that said rod tip (16) is shaped with a rounded geometry, such as an ogive, said fibre (17) being arranged in a uniform thickness.
3. Swab as claimed in claim 1, characterised in that said rod tip (16) is shaped
10 with a geometry at least partly truncated or with edges.
4. Swab as claimed in claim 1, characterised in that said layer of said fibre (17) has a thickness between 0.6 and 3 mm.
5. Swab as claimed in claim 1, characterised in that in said fibre layer (17), said fibre has a count between 1.7 and 3.3 Dtex.
- 15 6. Swab as claimed in claim 1, characterised in that in said layer (17), said fibre has a length and count variable from respectively 0.6 mm and 1.7 Dtex to provide a fine nap, to a length of 3 mm and a count of 3.3 Dtex to provide a long nap.
7. Swab as claimed in claim 1, characterised in that said fibre (17) is chosen from rayon, polyester, polyamide, carbon fibre, alginate; natural fibres such as cotton
20 and silk; or their mixtures.
8. Device for collecting and transporting biological specimens characterised by comprising a test-tube (10) containing a culture medium (11), and a swab (20) as claimed in one or more of the preceding claims.
9. Method for preparing a swab (20) as claimed in one or more of the preceding
25 claims characterised by comprising the steps of applying an adhesive to the tip (16) of said rod (14) of said swab (20) to be covered by fibre (17), and subjecting said swab (20) to flocking with the pre-selected fibre (17) in an electrostatic field.

1/1

Fig. 1





Fig. 2

INTERNATIONAL SEARCH REPORT

International Application No.

EP2004/003392

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61B10/00 B01L3/00 C12M1/30 A61M35/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B B01L C12M A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data ✓

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 749 655 A (CORASANITI VIRGINIA M ET AL) 7 June 1988 (1988-06-07) column 2, line 45 - column 4, line 2	1-9
A	US 5 009 846 A (GAVET LOUIS ET AL) 23 April 1991 (1991-04-23) column 1, line 55 - line 68 column 6, line 10 - line 22	1-4
A	EP 0 643 131 A (COPAN ITALIA SPA) 15 March 1995 (1995-03-15) cited in the application column 3, line 14 - column 4, line 34	1-9

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

2 July 2004

Date of mailing of the international search report

12/07/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Tragoustis, M

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4749655	A	07-06-1988	NONE	
US 5009846	A	23-04-1991	FR 2637687 A1	13-04-1990
			AT 86741 T	15-03-1993
			DE 68905300 D1	15-04-1993
			DE 68905300 T2	12-08-1993
			EP 0369836 A1	23-05-1990
			ES 2039904 T3	01-10-1993
			JP 2222839 A	05-09-1990
			JP 2775680 B2	16-07-1998
EP 0643131	A	15-03-1995	IT MI931934 A1	09-03-1995
			DE 69428958 D1	13-12-2001
			DE 69428958 T2	06-06-2002
			EP 0643131 A2	15-03-1995
			ES 2165372 T3	16-03-2002
			US 5627071 A	06-05-1997